


Single-LED

10-2119.1044

Distribution by
Farnell



<https://farnell.eao.com/component/10-2119.104...>

Your product:



10-2119.1044 Single-LED

Loading . . .

OPERATING-/INDICATION PART

Illumination colour: Yellow

ELECTRICAL CHARACTERISTICS

Forward voltage:

Operating voltage: 48 V AC/DC +10%

Operation current: 4 - 8 mA \pm 15 %

Lumi. Intensity: 180 mcd

MECHANICAL CHARACTERISTICS

Weight: 0.001 kg

CERTIFICATE

REACH: REACH compliant

RoHS: RoHS compliant

OTHER


Short Description: Single-LED, T5.6, Yellow, 48 V AC/DC +10%

Kind of illumination: Single-LED

Hints: For LED element fitting information see Application guidelines, LED polarity
Due to high surface temperatures, the series resistor must not be soldered directly to the terminals of the equipment (use a terminal plate)
When using AC/DC types with AC operation, slight flickering can occur
The luminous intensity stated is for when used with DC
Electrical and optical data are measured at 25 °C
The specified versions are built with a protection diode (halve wave rectifier) in series and the LED

Luminosity and wave length variations caused by LED manufacturing processes may cause slight differences regarding the illumination. The customer has to decide what resistor shall be used to the LED
Where supply voltages are over 48 V, a voltage-reduction element (external protective series resistor) must be used.

Wiring diagrams:



Dimension drawings:

