

# Single-LED

10-4H21.1032P

Distribution by  
Farnell



<https://farnell.eao.com/component/10-4H21.103...>

Your product:

---



## 10-4H21.1032P Single-LED

### OPERATING-/INDICATION PART

**Illumination colour:** Red

### ELECTRICAL CHARACTERISTICS

**Operating voltage:** 72 V AC/DC

**Operation current:** 2,2 mA -30%/+25%

**Lumi. Intensity:** 4 x 128 mcd

### MECHANICAL CHARACTERISTICS

**Weight:** 0.002 kg

### CERTIFICATE

**REACH:** REACH compliant

**RoHS:** RoHS compliant

### OTHER

**Short Description:** Single-LED, BA9s, Red, 72 V AC/DC

**Kind of illumination:** Multi-LED EN 50155

### Hints:

A suitable LED remover Part No. 700.006.0

The luminous intensity stated is for when used with DC

Electrical and optical data are measured at 25 °C

The specified 72 and 110 VAC/VDC versions are built with a bridge rectifier

The specified 72 and 110 VAC/VDC versions are built with a protection diode

In case one LED fails, the other pair of still functioning LED's is working. The light

output then is half in order to indicate the malfunction and shows this way the


need for replacement

Luminosity and wave length variations caused by LED manufacturing processes

may cause slight differences regarding the illumination. The customer has to

decide what resistor shall be used to the LED

**Wiring diagrams:**



**Dimension drawings:**

