

# Indicator

17-371351Z











## 17-371351Z Indicator

_	_	_		-
-	к	u	N	

Front dimension: Ø 18,3 mm

Front form: Round

Reflector: Plastic, Black

#### **MOUNTING**

Design: Raised

**Mounting cut-out:** Ø 16.2 mm

Mounting type: Panel mounting

#### **OPERATING-/INDICATION PART**

Lens: flush

Illumination colour: Green

### **ELECTRICAL CHARACTERISTICS**

**Operating voltage:** 24 V DC  $\pm 10 \%$ 

**Operation current:** 15 mA  $\pm$ 15 %

Lumi. Intensity: 980 mcd

**Polarity:** Anode (+) Brass plug-in connector

Cathode (-) Brass tinned plug-in connector

#### **MECHANICAL CHARACTERISTICS**

**Terminal:** Plug-in terminal, 2.8 x 0.8 mm

**Tightening torque:** Fixing nut max. 0.2 Nm

Weight:	0.007 kg
AMBIENT CONDITION	
IP Protection:	IP40 front side, IP65 front side, according to IEC 60529
Operating temperature:	– 20 °C + 60 °C
Storage temperature:	– 25 °C + 80 °C
CERTIFICATE	
Approbations:	UL
Conformities:	2011 / 65 / EC (RoHS), 2014 / 35 / EU (230 VAC)
REACH:	REACH compliant
RoHS:	RoHS compliant

#### **OTHER**

**Short Description:** Indicator, Ø 16.2 mm, Ø 18,3 mm, Round, Plug-in terminal, 2.8 x 0.8 mm, Green


Kind of illlumination: Single-LED

Hints: Connectors: Brass terminal = anode (+); brass tinned terminal = cathode (-)


IP67 front side gap between LED and reflector and gap between reflector and

frontplate sealed to IP67 when using the supplied gasket. The plastic is limited resistant to chemicals.


Wiring diagrams:



Mounting cut-outs:



### Dimension drawings:



A = Protection tube (only 230 VAC) B = 1 gasket C = flat

conical D = round