

Indicator

17-38135WZ











17-38135WZ Indicator

Round

Front dimension: Ø 18,3 mm

Reflector: Plastic, Black

MOUNTING

Front form:

Design: Raised

Mounting cut-out: Ø 16.2 mm

Mounting type: Panel mounting

OPERATING-/INDICATION PART

Lens: flush

Illumination colour: White

ELECTRICAL CHARACTERISTICS

Operating voltage: 24 V DC $\pm 10 \%$

Operation current: 14 mA \pm 15 %

Lumi. Intensity: 1290 mcd

Polarity: Anode (+) Brass plug-in connector

Cathode (-) Brass tinned plug-in connector

MECHANICAL CHARACTERISTICS

Terminal: Plug-in terminal, 2.8 x 0.8 mm

Tightening torque: Fixing nut max. 0.2 Nm

Weight:	0.007 kg	
AMBIENE CONDITION		
AMBIENT CONDITION		
IP Protection:	IP40 front side, IP65 front side, according to IEC 60529	
Operating temperature:	– 20 °C + 60 °C	
Storage temperature:	– 25 °C + 80 °C	
CERTIFICATE		
Approbations:	UL	
Conformities:	2011 / 65 / EC (RoHS), 2014 / 35 / EU (230 VAC)	
REACH:	REACH compliant	
RoHS:	RoHS compliant	

OTHER

Short Description: Indicator, Ø 16.2 mm, Ø 18,3 mm, Round, Plug-in terminal, 2.8 x 0.8 mm, White


Kind of illlumination: Single-LED

Hints: Connectors: Brass terminal = anode (+); brass tinned terminal = cathode (-)


IP67 front side gap between LED and reflector and gap between reflector and

frontplate sealed to IP67 when using the supplied gasket. The plastic is limited resistant to chemicals.


Wiring diagrams:



Mounting cut-outs:



Dimension drawings:



A = Protection tube (only 230 VAC) B = 1 gasket C = flat

conical D = round