

Your Expert Partner for Human Machine Interfaces

Actuator

18-060.0055L







https://farnell.eao.com/p/18-060.0055L

Your product:



18-060.0055L Actuator

PRODUCT RANGE

Product Status:	Phase-out
FRONT	
Front dimension:	Ø 19 mm
Front form:	Round
Front bezel colour:	Black
Front bezel material:	Plastic

MOUNTING

Design:	Flush
Mounting type:	Panel mounting

OPERATING-/INDICATION PART

Lens colour:	Green
Lens material:	Plastic
Lens illumination:	Illuminated
Lens shape:	Flush
Lens optics:	translucent
Illumination colour:	Green

ELECTRICAL CHARACTERISTICS


Operating voltage:

MECHANICAL CHARACTERISTICS

Terminal:

Weight:	0.002 kg	
AMBIENT CONDITION		
Operating temperature:	– 25 °C + 65 °C	
CERTIFICATE		
REACH:	REACH compliant	
RoHS:	RoHS compliant	
OTHER		
Short Description:	Actuator, Ø 19 mm, Flush, Illuminated, Green, Plastic, translucent, Round, Black, Plastic, Soldering terminal, Green	
Dimension:	Ø 13.8 mm	
Product attributes:	Luminosity and wave length variations caused by LED manufacturing processes may cause slight differences regarding the illumination. The customer has to decide what resistor shall be used to the LED	
Wiring diagrams:		
	+	


Soldering terminal



Component layouts:

(A) (B) 9 x 9 mm 19 x 19 mm 9 x 14 mm 09 mm 019 x 19 mm 019 x 19 mm (19 x 19 mm 019 x 19 mm (19 x 19 mm) (19 x 19 mm A = Terminals (rear side) B = Indicator

Mounting cut-outs:



Dimension drawings:

