


Actuator

18-

138.035











18-138.035 Actuator

| PRODUCT RANGE | ìΕ |
|---------------|----|
|---------------|----|

Front bezel colour:

| Product Status: | Phase-out |
|-----------------|-----------|
| | |
| | |
| FRONT | |

Black

Front dimension: Ø 9 mm
Front form: Round

Front bezel material: Plastic

MOUNTING

Design: Raised

Mounting type: Panel mounting

OPERATING-/INDICATION PART

Lens illumination: Illuminated

ELECTRICAL CHARACTERISTICS

Switching voltage and switching 100 mA at 42 VAC/VDC current:

Contacts: 1 NC

Switching rating: $42 \lor @ 0,1 A$

Electrical lifetime: ≥500 000 cycles of operation at 30 VDC, 100 mA, according to IEC 61058-1

Electric strength: 500 VAC, 50 Hz, 1 minute, as per IEC 60512-2-11 between all terminals and earth

MECHANICAL CHARACTERISTICS

| Terminal: | Soldering terminal |
|------------------------|---|
| Contact material: | Gold |
| Switching action: | Momentary |
| Switching system: | Snap-action switching element |
| Switching system: | The snap-action switching system was designed for switching low powers in electronic circuits. Single-break snap-action contact. |
| Mechanical lifetime: | 2 Mil. cycles of operation |
| Operating force: | 1.4 N |
| Operating Travel: | ca. 2.2 mm ± 0.2 mm |
| Tightening torque: | Fixing nut max. 0.2 Nm |
| Wire cross section: | Max. wire cross-section 2 wires with 0.5 mm Max. wire cross-section of stranded cable 1 x 0.75 mm 2 Wire cross-section of terminal 1,6 x 0,4 mm 2 |
| Weight: | 0.002 kg |
| | |
| AMBIENT CONDITION | |
| IP front protection: | IP40, according to IEC 60529 |
| Operating temperature: | – 25 °C + 65 °C |
| Storage temperature: | – 40 °C + 80 °C |
| Shock resistance: | 50 g for 11 ms, as per DIN / EN 60068-2-27 (Single impacts, semi-sinusoidal) |
| Vibration resistance: | 10 g at 10 Hz2000 Hz, amplitude 0.75 mm (Sinusoidal), according to DIN EN 60512-4-4 |
| | |
| CERTIFICATE | |
| Conformities: | 2011 / 65 / EC (RoHS), 2014 / 35 / EU (LVD) for version 230 VAC |
| REACH: | REACH compliant |
| RoHS: | RoHS compliant |
| | |
| | |

OTHER

Actuator, \varnothing 9 mm, Illuminated, Round, Black, Plastic, 1 NC, Momentary, Soldering terminal, IP40, according to IEC 60529 **Short Description:**

Internal size: Ø 7,5 mm

Black Housing colour:


Housing material:

Plastic


Product attributes:

+/- terminals are not connected

Wiring diagrams:



Component layouts:




A = Terminals (rear side)

B = Illuminated pushbutton

C = x = Contact No.

D = 2 = Normally open E = 4 = Normally close

Mounting cut-outs:



Dimension drawings:

