

Actuator

31-

716.0292









31-716.0292 Actuator

P	R	Ö	D	u	C.	ГΙ	R	Δ	N	G	F

Product Status: Not Recommended for new design

FRONT

Front dimension: 24 mm x 18 mm

Front form: Rectangular

Front bezel colour: Black

Front bezel material: Plastic

MOUNTING

Design: Raised

Mounting cut-out: Ø 16 mm

Mounting type: Panel mounting

OPERATING-/INDICATION PART

Lens illumination: Illuminated

ELECTRICAL CHARACTERISTICS

Switching voltage and switching

current:

250 VAC, 5 A (ohmic)

250 VAC, 3 A (Soldering terminal) 250 VAC, 2 A (inductive, cos(phi) = 0.7) 125 VAC, 3 A (inductive, cos(phi) = 0.7) 220 VDC, 0.1 A (inductive, L:R = 30 ms) 60 VDC, 0.7 A (inductive, L:R = 30 ms)

60 VDC, 0.7 A (inductive, L:R = 30 ms) 24 VDC, 2 A (inductive, L:R = 30 ms)

Contacts: 2 NC / 2 NO

Rated Operational Voltage Ue:

250 VAC/VDC

Switching rating: 250 V @ 5 A

Electrical lifetime: 50 000 cycles of operation

Electric strength: 2500 VAC, 50 Hz, 1 minute, as per IEC 60512-2-11 between all terminals and

earth

Protection class:

Standards: According to EN/IEC 61058-1

Thermal current Ith: 5 A

MECHANICAL CHARACTERISTICS

Terminal: Universal soldering terminal

Contact material: Gold

Switching action: Maintained

Switching system: Snap-action switching element

Switching system: Self-cleaning, double-break snap action switching system (contact opening width 2

mm x 0.5 mm), 1 normally closed and 1 normally open contact per element.

Mechanical lifetime: 1 Mil. cycles of operation

Operating force: 2 N ... 5,5 N, depending on the number of switching elements

Operating Travel: ca. 3 mm

Tightening torque: Fixing nut max. 0.5 Nm

Wire cross section: Max. wire cross-section 1 wire with 1.5 mm

Max. wire cross-section of stranded cable 2 of 0.75 mm² or 1 x 1.0 mm²

Weight: 0.01 kg

AMBIENT CONDITION

IP Protection: IP40 front side, IP67 with front protective cap

Operating temperature: - 25 °C, mounted as a block, make sure the heat can escape freely

Storage temperature: $-40 \, ^{\circ}\text{C} \dots + 85 \, ^{\circ}\text{C}$

Shock resistance: 15 g for 11 ms, as per IEC 60512-4-3, IEC 60068-2-27 (Single impacts, semi-

sinusoidal)

Vibration resistance: 10 g at 10 Hz...2000 Hz, amplitude 1.5 mm (Sinusoidal), according to DIN EN

60512-4-4, DIN EN 60068-2-6

Climate resistance: Standard condition according to IEC 60068-2-3

Changing condition according to IEC 60068-2-14

CERTIFICATE

Approbations: CB (IEC 61058-1), CSA, DNV, ENEC (EN 61058-1), UL

Conformities: CE, UKCA, 2011 / 65 / EC (RoHS), 2014 / 35 / EU (LVD)

REACH: REACH compliant

RoHS: RoHS compliant

OTHER

Short Description: Actuator, Ø 16 mm, 24 mm x 18 mm, Illuminated, Rectangular, Black, Plastic, 2

NC / 2 NO, Maintained, Universal soldering terminal

Internal size: 21,5 mm x 15,3 mm


Housing colour: Black

max. number of switching

elements:

1

Wiring diagrams:



Component layouts:



A = Terminals (rear side)


B = Diode block

C = Anti twist device only 18 mm x 24


mm

D = Drilling plan (component side)

Mounting cut-outs:



Dimension drawings:



A = Solder terminal
B = Plug-in terminal 2.8 mm x 0.5 mm
C = Universal terminal 2.0 mm x 0.5 mm
D = Universal-Solder terminal