

# Actuator

45-2131.4F10.000











## 45-2131.4F10.000 Actuator

_	_	_		-
-	к	u	N	

Front dimension: Ø 38 mm

Front form: Round

Front bezel colour: Sand grey

Front bezel material: Metal

#### **MOUNTING**

Design: Flush

Mounting cut-out: Ø 30.5 mm

Mounting type: Panel mounting

## **OPERATING-/INDICATION PART**

Lens colour: Black

Lens material: Plastic

Lens illumination: Non illuminated

Lens shape: Flush

**Lens optics:** opaque

### **MECHANICAL CHARACTERISTICS**

Switching action: Momentary

**Switching system:** Slow-make switching element

**Mechanical lifetime:** 500 000 cycles of operation

**Operating frequency:** Max. 3 600/h

AMBIENT CONDITION  IP front protection:  IP66, IP67, IP69K  Operating temperature:  - 25 °C + 70 °C  Storage temperature:  - 40 °C + 80 °C  Shock resistance:  According to IEC 60068-2-27: Sinusoidal half-wave 50 g / 11 ms  Vibration resistance:  According to IEC 60068-2-6: 20 500 Hz: 5 g  Climate resistance:  During operation according to IEC 60721: 3K6, 3C3, 3S2, 3M6  CERTIFICATE  REACH:  REACH:  REACH compliant  OTHER  Short Description:  Actuator, Ø 30.5 mm, Ø 38 mm, Flush, Non illuminated, Black, Plastic, opaque Round, Sand grey, Metal, Momentary, IP66, IP67, IP69K  Housing colour:  Housing material:  Metal  Hints:  Front panel thickness 1 6 mm  Wiring diagrams:			
Operating temperature: - 25 °C + 70 °C  Storage temperature: - 40 °C + 80 °C  Shock resistance: According to IEC 60068-2-27: Sinusoidal half-wave 50 g / 11 ms  Vibration resistance: According to IEC 60068-2-6: 20 500 Hz: 5 g  Climate resistance: During operation according to IEC 60721: 3K6, 3C3, 3S2, 3M6  CERTIFICATE  REACH: REACH: ROHS: ROHS compliant  OTHER  Short Description: Actuator, Ø 30.5 mm, Ø 38 mm, Flush, Non illuminated, Black, Plastic, opaque Round, Sand grey, Metal, Momentary, IP66, IP67, IP69K  Housing colour: Housing material: Metal  Hints: Front panel thickness 1 6 mm	AMBIENT CONDITION		
Storage temperature: - 40 °C + 80 °C  Shock resistance: According to IEC 60068-2-27: Sinusoidal half-wave 50 g / 11 ms  Vibration resistance: According to IEC 60068-2-6: 20 500 Hz: 5 g  Climate resistance: During operation according to IEC 60721: 3K6, 3C3, 3S2, 3M6  CERTIFICATE  REACH: REACH: REACH compliant  RoHS: RoHS compliant  OTHER  Short Description: Actuator, Ø 30.5 mm, Ø 38 mm, Flush, Non illuminated, Black, Plastic, opaque Round, Sand grey, Metal, Momentary, IP66, IP67, IP69K  Housing colour: Housing material: Metal  Hints: Front panel thickness 1 6 mm	IP front protection:	IP66, IP67, IP69K	
Shock resistance:  According to IEC 60068-2-27: Sinusoidal half-wave 50 g / 11 ms  Vibration resistance:  According to IEC 60068-2-6: 20 500 Hz: 5 g  Climate resistance:  During operation according to IEC 60721: 3K6, 3C3, 3S2, 3M6  CERTIFICATE  REACH:  REACH:  REACH compliant  RoHS:  ROHS compliant  OTHER  Short Description:  Actuator, Ø 30.5 mm, Ø 38 mm, Flush, Non illuminated, Black, Plastic, opaque Round, Sand grey, Metal, Momentary, IP66, IP67, IP69K  Housing colour:  Housing material:  Metal  Hints:  Front panel thickness 1 6 mm	Operating temperature:	– 25 °C + 70 °C	
Vibration resistance: According to IEC 60068-2-6: 20 500 Hz: 5 g  Climate resistance: During operation according to IEC 60721: 3K6, 3C3, 3S2, 3M6  CERTIFICATE  REACH: REACH compliant  RoHS: RoHS compliant  OTHER  Short Description: Actuator, Ø 30.5 mm, Ø 38 mm, Flush, Non illuminated, Black, Plastic, opaque Round, Sand grey, Metal, Momentary, IP66, IP67, IP69K  Housing colour: Silver  Housing material: Metal  Hints: Front panel thickness 1 6 mm	Storage temperature:	– 40 °C + 80 °C	
Climate resistance:  During operation according to IEC 60721: 3K6, 3C3, 3S2, 3M6  CERTIFICATE  REACH: REACH: REACH compliant  RoHS: ROHS compliant  OTHER  Short Description: Actuator, Ø 30.5 mm, Ø 38 mm, Flush, Non illuminated, Black, Plastic, opaque Round, Sand grey, Metal, Momentary, IP66, IP67, IP69K  Housing colour: Silver  Housing material: Metal  Hints: Front panel thickness 1 6 mm	Shock resistance:	According to IEC 60068-2-27: Sinusoidal half-wave 50 g / 11 ms	
CERTIFICATE  REACH: REACH compliant  RoHS: RoHS compliant  OTHER  Short Description: Actuator, Ø 30.5 mm, Ø 38 mm, Flush, Non illuminated, Black, Plastic, opaque Round, Sand grey, Metal, Momentary, IP66, IP67, IP69K  Housing colour: Silver  Housing material: Metal  Hints: Front panel thickness 1 6 mm	Vibration resistance:	According to IEC 60068-2-6: 20 500 Hz: 5 g	
REACH: REACH compliant  RoHS: RoHS compliant  OTHER  Short Description: Actuator, Ø 30.5 mm, Ø 38 mm, Flush, Non illuminated, Black, Plastic, opaque Round, Sand grey, Metal, Momentary, IP66, IP67, IP69K  Housing colour: Silver  Housing material: Metal  Hints: Front panel thickness 1 6 mm	Climate resistance:	During operation according to IEC 60721: 3K6, 3C3, 3S2, 3M6	
REACH: REACH compliant  RoHS: RoHS compliant  OTHER  Short Description: Actuator, Ø 30.5 mm, Ø 38 mm, Flush, Non illuminated, Black, Plastic, opaque Round, Sand grey, Metal, Momentary, IP66, IP67, IP69K  Housing colour: Silver  Housing material: Metal  Hints: Front panel thickness 1 6 mm			
RoHS: RoHS compliant  OTHER  Short Description: Actuator, Ø 30.5 mm, Ø 38 mm, Flush, Non illuminated, Black, Plastic, opaque Round, Sand grey, Metal, Momentary, IP66, IP67, IP69K  Housing colour: Silver  Housing material: Metal  Hints: Front panel thickness 1 6 mm	CERTIFICATE		
OTHER  Short Description:  Actuator, Ø 30.5 mm, Ø 38 mm, Flush, Non illuminated, Black, Plastic, opaque Round, Sand grey, Metal, Momentary, IP66, IP67, IP69K  Housing colour:  Housing material:  Metal  Front panel thickness 1 6 mm	REACH:	REACH compliant	
Short Description:       Actuator, Ø 30.5 mm, Ø 38 mm, Flush, Non illuminated, Black, Plastic, opaque Round, Sand grey, Metal, Momentary, IP66, IP67, IP69K         Housing colour:       Silver         Housing material:       Metal         Hints:       Front panel thickness 1 6 mm	RoHS:	RoHS compliant	
Short Description:       Actuator, Ø 30.5 mm, Ø 38 mm, Flush, Non illuminated, Black, Plastic, opaque Round, Sand grey, Metal, Momentary, IP66, IP67, IP69K         Housing colour:       Silver         Housing material:       Metal         Hints:       Front panel thickness 1 6 mm			
Round, Sand grey, Metal, Momentary, IP66, IP67, IP69K  Housing colour: Silver  Housing material: Metal  Hints: Front panel thickness 1 6 mm	OTHER		
Housing material: Metal  Hints: Front panel thickness 1 6 mm	Short Description:	Actuator, Ø 30.5 mm, Ø 38 mm, Flush, Non illuminated, Black, Plastic, opaque, Round, Sand grey, Metal, Momentary, IP66, IP67, IP69K	
Hints: Front panel thickness 1 6 mm	Housing colour:	Silver	
	Housing material:	Metal	
Wiring diagrams:	Hints:	Front panel thickness 1 6 mm	
Dimension drawings:		<b>_</b>	

0.074 kg

Weight:

