


Actuator

45-2134.1140.000









Your product:



45-2134.1140.000 Actuator

FRONT

Front dimension: Ø 29,5 mm

Front form: Round

Front bezel colour: Black

Front bezel material: Plastic

MOUNTING

Design: Raised

Mounting cut-out: Ø 22.3 mm

Mounting type: Panel mounting

OPERATING-/INDICATION PART

Lens colour: Yellow

Lens material: Plastic

Lens illumination: Non illuminated

Lens shape: Flush

Lens optics: opaque

Lens type: Level with front bezel


MECHANICAL CHARACTERISTICS

Switching action: Maintained

Switching system: Slow-make switching element

Mechanical lifetime: 10 Mil. cycles of operation

Weight:	0.017 kg
AMBIENT CONDITION	
IP front protection:	IP66, IP67, IP69K
Operating temperature:	– 25 °C + 70 °C
Storage temperature:	– 40 °C + 80 °C
Shock resistance:	According to IEC 60068-2-27: Sinusoidal half-wave 50 g / 11 ms
Vibration resistance:	According to IEC 60068-2-6: 20 500 Hz: 5 g
Climate resistance:	During operation according to IEC 60721: 3K6, 3C3, 3S2, 3M6
CERTIFICATE	
REACH:	REACH compliant
RoHS:	RoHS compliant
OTHER	
Short Description:	Actuator, \varnothing 22.3 mm, \varnothing 29,5 mm, Flush, Non illuminated, Yellow, Plastic, opaque, Round, Black, Plastic, Maintained, IP66, IP67, IP69K
Housing colour:	Black
Housing material:	Plastic
Hints:	Push to unlatch
Wiring diagrams:	
	E-~-
Mounting cut-outs:	



Dimension drawings:

