

# Actuator

45-2134.4F50.000











## 45-2134.4F50.000 Actuator

Е	D	0	N	٦
г	п	v	14	

Front dimension: Ø 38 mm

Front form: Round

Front bezel colour: Sand grey

Front bezel material: Metal

#### **MOUNTING**

Design: Flush

Mounting cut-out: Ø 30.5 mm

Mounting type: Panel mounting

## **OPERATING-/INDICATION PART**

Lens colour: Green

Lens material: Plastic

Lens illumination: Non illuminated

Lens shape: Flush

**Lens optics:** opaque

### **MECHANICAL CHARACTERISTICS**

Switching action: Maintained

**Switching system:** Slow-make switching element

**Mechanical lifetime:** 10 Mil. cycles of operation

**Operating frequency:** Max. 1 800/h

Weight:	0.071 kg		
AMBIENT CONDITION			
IP front protection:	IP66, IP67, IP69K		
Operating temperature:	– 25 °C + 70 °C		
Storage temperature:	– 40 °C + 80 °C		
Shock resistance:	According to IEC 60068-2-27: Sinusoidal half-wave 50 g / 11 ms		
Vibration resistance:	According to IEC 60068-2-6: 20 500 Hz: 5 g		
Climate resistance:	During operation according to IEC 60721: 3K6, 3C3, 3S2, 3M6		
CERTIFICATE			
REACH:	REACH compliant		
RoHS:	RoHS compliant		
OTHER			
Short Description:	Actuator, Ø 30.5 mm, Ø 38 mm, Flush, Non illuminated, Green, Plastic, opaque, Round, Sand grey, Metal, Maintained, IP66, IP67, IP69K		
Housing colour:	Silver		
Housing material:	Metal		
Hints:	Push to unlatch		
Wiring diagrams:			
	E~-		

Dimension drawings:

