

# Actuator

45-2630.29K0.000











# 45-2630.29K0.000 Actuator

Loading . . .

	-	

Front dimension: Ø 40 mm

Front form: Round

Front bezel colour: Silver

Front bezel material: Metal

#### **MOUNTING**

Design: Raised

Mounting cut-out: Ø 22.3 mm

Mounting type: Panel mounting

### **OPERATING-/INDICATION PART**

Lens colour: Colourless

Lens material: Plastic

Lens illumination: Illuminated

Lens shape: Mushroom-head

Lens optics: transparent

## **MECHANICAL CHARACTERISTICS**

Switching action: Maintained

Switching system: Slow-make switching element

Release type: Pull unlock

**Mechanical lifetime:** 500 000 cycles of operation

Operating frequency: Max. 1 800/h

Weight: 0.061 kg

#### **AMBIENT CONDITION**

**IP front protection:** IP66, IP67, IP69K

**Operating temperature:**  $-25 \, ^{\circ}\text{C} \, ... + 70 \, ^{\circ}\text{C}$ 

Storage temperature:  $-40 \, ^{\circ}\text{C} \dots + 80 \, ^{\circ}\text{C}$ 

**Shock resistance:** According to IEC 60068-2-27: Sinusoidal half-wave 50 g / 11 ms

**Vibration resistance:** According to IEC 60068-2-6: 20 ... 500 Hz: 5 g

**Climate resistance:** During operation according to IEC 60721: 3K6, 3C3, 3S2, 3M6

#### **CERTIFICATE**

**REACH:** REACH compliant

RoHS: RoHS compliant

### **OTHER**


Short Description: Actuator, Ø 22.3 mm, Ø 40 mm, Mushroom-head, Illuminated, Colourless, Plastic,

transparent, Round, Silver, Metal, Maintained, IP66, IP67, IP69K, Pull unlock


Housing colour: Silver

Housing material: Metal

Wiring diagrams:



## Mounting cut-outs:



# Dimension drawings:

