

Actuator

45-2631.2AG0.000











45-2631.2AG0.000 Actuator

_	_	_		-
-	к	u	N	

Front dimension: Ø 60 mm

Front form: Round

Front bezel colour: Silver

Front bezel material: Metal

MOUNTING

Design: Raised

Mounting cut-out: Ø 22.3 mm

Mounting type: Panel mounting

OPERATING-/INDICATION PART

Lens colour: Yellow

Lens material: Plastic

Lens illumination: Illuminated

Lens shape: Mushroom-head

Lens optics: transparent

MECHANICAL CHARACTERISTICS

Switching action: Momentary

Switching system: Slow-make switching element

Mechanical lifetime: 10 Mil. cycles of operation

Operating frequency: Max. 3 600/h

Weight:	0.055 kg
---------	----------

AMBIENT CONDITION

IP front protection: IP66, IP67, IP69K

Operating temperature: $-25 \, ^{\circ}\text{C} \, ... + 70 \, ^{\circ}\text{C}$

Storage temperature: $-40 \,^{\circ}\text{C} \dots + 80 \,^{\circ}\text{C}$

Shock resistance: According to IEC 60068-2-27: Sinusoidal half-wave 50 g / 11 ms

Vibration resistance: According to IEC 60068-2-6: 20 ... 500 Hz: 5 g

Climate resistance: During operation according to IEC 60721: 3K6, 3C3, 3S2, 3M6

CERTIFICATE

REACH: REACH compliant

RoHS: RoHS compliant

OTHER


Short Description: Actuator, Ø 22.3 mm, Ø 60 mm, Mushroom-head, Illuminated, Yellow, Plastic,

transparent, Round, Silver, Metal, Momentary, IP66, IP67, IP69K


Housing colour: Silver

Housing material: Metal

Wiring diagrams:



Mounting cut-outs:



Dimension drawings:

