

Actuator

45-
2819.4C20.003

Distribution by
Farnell



<https://farnell.eao.com/component/45-2819.4C2...>

Your product:



45-2819.4C20.003 Actuator

FRONT

| | |
|------------------------------|-----------|
| Front dimension: | Ø 38 mm |
| Front form: | Round |
| Front bezel colour: | Sand grey |
| Front bezel material: | Metal |

MOUNTING

| | |
|--------------------------|----------------|
| Design: | Flush |
| Mounting cut-out: | Ø 30.5 mm |
| Mounting type: | Panel mounting |

OPERATING-/INDICATION PART

| | |
|------------------------|---------|
| Lever colour: | Red |
| Lever material: | plastic |
| Lever shape: | short |

MECHANICAL CHARACTERISTICS

| | |
|-----------------------------|--------------------------------------|
| Switching action: | Maintained - Rest - Maintained |
| Switching positions: | 3 positions |
| Switching angle: | 45° left / 45° right |
| Mechanical lifetime: | 1 Mil. cycles of operation (RCC/RPB) |
| Operating frequency: | 1 800/h |
| Weight: | 0.062 kg |

AMBIENT CONDITION


| | |
|-------------------------------|--|
| IP front protection: | IP66, IP67, IP69K |
| Operating temperature: | - 25 °C ... + 70 °C |
| Storage temperature: | - 40 °C ... + 80 °C |
| Shock resistance: | According to IEC 60068-2-27: Sinusoidal half-wave 50 g / 11 ms |
| Vibration resistance: | According to IEC 60068-2-6: 10 ... 500 Hz: 5 g |
| Climate resistance: | During operation according to IEC 60721: 3K6, 3C3, 3S2, 3M6 |

CERTIFICATE


| | |
|---------------|-----------------|
| REACH: | REACH compliant |
| RoHS: | RoHS compliant |

OTHER

| | |
|-----------------------------|---|
| Short Description: | Actuator, Ø 30.5 mm, Ø 38 mm, optional illuminative, Red, short, Round, Sand grey, Metal, Maintained - Rest - Maintained, IP66, IP67, IP69K |
| Housing material: | Metal |
| Hints: | Front panel thickness 1 ... 6 mm |
| Switching positions: | |



Wiring diagrams:



Dimension drawings:

