

# Actuator

45-  
290K.1000.116

Distribution by  
Farnell



<https://farnell.eao.com/p/45-290K.1000.116>

Your product:

---



## 45-290K.1000.116 Actuator

### FRONT

Front dimension:	Ø 29,5 mm
Front form:	Round
Front bezel colour:	Black
Front bezel material:	Plastic

### MOUNTING

Design:	Raised
Mounting cut-out:	Ø 22.3 mm
Mounting type:	Panel mounting

### MECHANICAL CHARACTERISTICS

Switching action:	Rest (a) - Momentary
Switching positions:	2 positions
Switching angle:	45° right
Mechanical lifetime:	1 Mil. cycles of operation
Operating frequency:	1 800/h
Weight:	0.054 kg

### AMBIENT CONDITION

IP front protection:	IP66, IP67, IP69K
Operating temperature:	- 25 °C ... + 70 °C
Storage temperature:	- 40 °C ... + 80 °C

**Shock resistance:**

According to IEC 60068-2-27: Sinusoidal half-wave 50 g / 11 ms

**Vibration resistance:**

According to IEC 60068-2-6: 10 ... 500 Hz: 5 g

**Climate resistance:**

During operation according to IEC 60721: 3K6, 3C3, 3S2, 3M6

**CERTIFICATE****REACH:**

REACH compliant

**RoHS:**

RoHS compliant

**OTHER****Short Description:**


Actuator, Ø 22.3 mm, Ø 29,5 mm, Round, Black, Plastic, Rest (a) - Momentary, IP66, IP67, IP69K

**Housing material:**

Plastic

**Hints:**

The standard lock: RONIS, T254

**Switching positions:****Wiring diagrams:****Mounting cut-outs:**



**Dimension drawings:**

