

# Actuator

45-2C36.2820.000









## Your product:



# 45-2C36.2820.000 Actuator

Front dimension: Ø 34 mm

Front form: Round

Front bezel colour: Silver

Front bezel material: Metal

#### **MOUNTING**

Mounting type: Panel mounting

#### **OPERATING-/INDICATION PART**

Lens colour: Red

Lens material: Plastic

Lens illumination: Non illuminated

**Lens shape:** Mushroom-head

**Lens optics:** opaque

#### **MECHANICAL CHARACTERISTICS**

Switching action: Maintained

Release type: Twist to unlock


**Mechanical lifetime:** 300 000 cycles of operation

**Operating frequency:** Max. 600/h

**Weight:** 0.094 kg

### **AMBIENT CONDITION**

Operating temperature:	– 25 °C + 70 °C	
Storage temperature:	– 40 °C + 80 °C	
Shock resistance:	According to IEC 60068-2-27: Sinusoidal half-wave 50 g / 11 ms	
Vibration resistance:	According to IEC 60068-2-6: 2 500 Hz: 5 g	
Climate resistance:	During operation according to IEC 60721: 3K6, 3C3, 3S2, 3M6	
CERTIFICATE		
REACH:	REACH compliant	
RoHS:	RoHS compliant	
OTHER		
Short Description:	Actuator, $\varnothing$ 34 mm, Mushroom-head, Non illuminated, Red, Plastic, opaque, Round, Silver, Metal, Maintained, Twist to unlock	
Dimension:	Ø 34 mm	
Housing colour:	Silver	
Housing material:	Metal	
Product attributes:	Twist to unlock clockwise	
Hints:	Application as per DIN EN ISO 13850 and EN 60204-1	
Wiring diagrams:	<u></u>	
Mounting cut-outs:		



### Dimension drawings:

