

# Actuator

45-  
482.1810

Distribution by  
Farnell



<https://farnell.eao.com/component/45-482.1810...>

Your product:

---



## 45-482.1810 Actuator

### FRONT

<b>Front dimension:</b>	85 mm x 85 mm
<b>Front form:</b>	Square

### MOUNTING

<b>Design:</b>	Raised
<b>Mounting cut-out:</b>	Ø 22.3 mm
<b>Component mounting type:</b>	Base mounting
<b>Mounting type:</b>	Panel mounting

### OPERATING-/INDICATION PART

<b>Lens colour:</b>	Red
<b>Lens material:</b>	Plastic
<b>Lens illumination:</b>	Non illuminated
<b>Lens optics:</b>	opaque

### ELECTRICAL CHARACTERISTICS

<b>Rated Operational Voltage Ue:</b>	At AC: rated value 5 ... 500 V At DC: rated value 5 ... 500 V
--------------------------------------	--

### MECHANICAL CHARACTERISTICS

<b>Switching action:</b>	Maintained
<b>Switching system:</b>	Slow-make switching element
<b>Release type:</b>	Pull unlock

**Weight:** 0.414 kg

## AMBIENT CONDITION

**IP front protection:** IP66, IP67, IP69K

**Storage temperature:** - 40 °C ... + 80 °C

**Shock resistance:** According to IEC 60068-2-27: Sinusoidal half-wave 50 g / 11 ms

**Vibration resistance:** According to IEC 60068-2-6: 10 ... 500 Hz: 5 g

**Climate resistance:** During operation according to IEC 60721: 3K6, 3C3, 3S2, 3M6, 3B2

## CERTIFICATE

**REACH:** REACH compliant

**RoHS:** RoHS compliant

## OTHER

**Short Description:** Actuator, Ø 22.3 mm, 85 mm x 85 mm, Non illuminated, Red, Plastic, opaque, Square, Maintained, IP66, IP67, IP69K, Pull unlock

**Housing colour:** Yellow

**Housing material:** Plastic

**Product attributes:** Pull release

**Dimension drawings:**

