

# Pendant control

46-447.1418

Distribution by  
Farnell



<https://farnell.eao.com/component/46-447.1418...>

Your product:

---



## 46-447.1418 Pendant control

*Loading ...*

### FRONT

**Colour:** Yellow

### MOUNTING

**Mounting cut-out:** Ø 22 mm

**Mounting type:** Panel mounting

### ELECTRICAL CHARACTERISTICS

**Rated insulation voltage  $U_i$ :**  $U_i$  300V -  $U_{imp}$  2.5KV (IEC-EN60947-1)

**Pollution degree:** 3

**Protection class:** II, according to EN / IEC 61140

### MECHANICAL CHARACTERISTICS

**Tightening torque:** 0.8 ... 1.2 Nm (7.1÷10.6 Lb-in)

**Weight:** 0.2 kg

### AMBIENT CONDITION

**IP front protection:** IP65, IP66

**IK front protection:** IK08

**Operating temperature:** - 35 °C ... + 80 °C

### CERTIFICATE

**Approbations:** CSA, UL

**Conformities:** CE  
**REACH:** REACH compliant  
**RoHS:** RoHS compliant  
**Standards:** CSA C22-2, IEC EN 60204-1, IEC EN 60947-1, IEC EN 60947-5-1, UL508

**OTHER**

**Short Description:** Pendant control  
**Number of holes:** 3  
**Dimension:** 83 mm x 137 mm  
**Housing material:** Plastic  
**Product attributes:** Suitable for outdoor applications  
**Dimension drawings:**

