

# Illumination element, 24 V

46-580.1H21

Distribution by  
Farnell



<https://farnell.eao.com/component/46-580.1H21...>

Your product:

---



## 46-580.1H21

### Illumination element, 24 V

#### MOUNTING

**Mounting type:** Panel mounting

#### OPERATING-/INDICATION PART

**Illumination colour:** Green

#### ELECTRICAL CHARACTERISTICS

**Operating voltage:** 24 V AC/DC -20% / +10%

**Protection class:** II, according to EN / IEC 61140

#### MECHANICAL CHARACTERISTICS

**Weight:** 0.147 kg

#### AMBIENT CONDITION

**IP front protection:** IP44

**IK front protection:** IK07

**Operating temperature:** - 25 °C ... + 65 °C

#### CERTIFICATE

**Conformities:** CE

**Standards:** EN 55015, EN 61000-3-2, EN 61000-3-3, EN 61547, IEC EN 60947-1, IEC EN 60947-5-1, IEC EN 62471

## OTHER

|                            |   |
|----------------------------|---|
| <b>Short Description:</b>  | Illumination element, 24 V, Ø 75 mm x 75 mm, Panel mounting, 24 V AC/DC -20% / +10% |
| <b>Titel Accessory:</b>    | Illumination element, 24 V  |
| <b>Dimension:</b>          | Ø 75 mm x 75 mm   |
| <b>Housing material:</b>   | Plastic   |
| <b>Product attributes:</b> | For Signal Light Tower  |