

Illumination element, 24 V

46-580.1K21

Distribution by
Farnell



<https://farnell.eao.com/component/46-580.1K21...>

Your product:



46-580.1K21 Illumination element, 24 V

Loading ...

MOUNTING

Mounting type: Panel mounting

OPERATING-/INDICATION PART

Illumination colour: Colourless

ELECTRICAL CHARACTERISTICS

Forward voltage:

Operating voltage: 24 V AC/DC -20% / +10%

Protection class: II, according to EN / IEC 61140

MECHANICAL CHARACTERISTICS

Weight: 0.147 kg

AMBIENT CONDITION

IP front protection: IP44

IK front protection: IK07

Operating temperature: - 25 °C ... + 65 °C

CERTIFICATE

Conformities: CE

Standards: EN 55015, EN 61000-3-2, EN 61000-3-3, EN 61547, IEC EN 60947-1, IEC EN 60947-5-1, IEC EN 62471

OTHER

| | |
|----------------------------|---|
| Short Description: | Illumination element, 24 V, Ø 75 mm x 75 mm, Panel mounting, 24 V AC/DC -20% / +10% |
| Titel Accessory: | Illumination element, 24 V |
| Dimension: | Ø 75 mm x 75 mm |
| Housing material: | Plastic |
| Product attributes: | For Signal Light Tower |