

# Actuator

704.011.818











## 704.011.818 Actuator

	_	_		-
ь.	к	()	N	

Front dimension:  $\varnothing$  35 mm

Front form: Round

Front bezel colour: Nature

Front bezel material: Aluminium

#### **MOUNTING**

Design: Flush

Mounting cut-out: Ø 30.5 mm

Mounting type: Panel mounting

## **OPERATING-/INDICATION PART**

Lens colour: Nature

Lens material: Aluminium

Lens illumination: Non illuminated

Lens shape: Flush

Lens optics: opaque

### **ELECTRICAL CHARACTERISTICS**


Standards: The switches comply with the "Standards for low-voltage switching devices" DIN

EN 60947-1

#### **MECHANICAL CHARACTERISTICS**

Switching action: Momentary


Mechanical lifetime:	≤3 Mil. cycles of operation	
Operating force:	8 N	
Operating Travel:	ca. 5.8 mm ± 0.2 mm	
Weight:	0.03 kg	
AMBIENT CONDITION		
IP Protection:	IP65 front side	
Operating temperature:	– 40 °C + 55 °C	
Storage temperature:	– 40 °C + 85 °C	
CERTIFICATE		
REACH:	REACH compliant	
RoHS:	RoHS compliant	
OTHER		
Short Description:	Actuator, $\varnothing$ 30.5 mm, $\varnothing$ 35 mm, Flush, Non illuminated, Nature, Aluminium, opaque, Round, Nature, Aluminium, anodised, Momentary	
Housing colour:	Grey	
Housing material:	Plastic	
Hints:	Max. 3 switching elements can be clipped on The colour of anodised aluminium parts can vary due to technical production reasons	
max. number of switching elements:	3	
Wiring diagrams:  Mounting cut-outs:	E	



A = Screw terminal

B = Push-in terminal (PIT)
C = Plug-in terminal 6.3 mm x 0.8 mm
D = Double plug-in terminal 6.3 mm x 0.8

## Dimension drawings:



A = Screw terminal