

## Actuator

704.032.2









Switching action:

Mechanical lifetime:



# 704.032.2 Actuator

K	
FRONT	
Front dimension:	Ø 29 mm
Front form:	Round
Front bezel colour:	Nature
Front bezel material:	Aluminium
MOUNTING	
Design:	Raised
Mounting type:	Panel mounting
OPERATING-/INDICATION PART	
Lens colour:	Red
Lens material:	Plastic
Lens illumination:	Illuminated
Lens shape:	Flush
Lens optics:	transparent
ELECTRICAL CHARACTERISTICS	
Standards:	The switches comply with the "Standards for low-voltage switching devices" DIN
	EN 60947-1
MECHANICAL CHARACTERISTICS	

Momentary

≤3 Mil. cycles of operation

Operating force: 8 N

**Operating Travel:** ca. 5.8 mm  $\pm$  0.2 mm

**Weight:** 0.034 kg

#### **AMBIENT CONDITION**

**IP Protection:** IP65 front side

**Operating temperature:**  $-40 \, ^{\circ}\text{C} \, ... + 55 \, ^{\circ}\text{C}$ 

Storage temperature:  $-40 \, ^{\circ}\text{C} \dots + 85 \, ^{\circ}\text{C}$ 

#### **CERTIFICATE**

**REACH:** REACH compliant

RoHS: RoHS compliant

#### **OTHER**

Short Description: Actuator, Ø 29 mm, Flush, Illuminated, Red, Plastic, transparent, Round, Nature,

Aluminium, anodised, Momentary

Housing colour: Grey

Housing material: Plastic

**Hints:** Frontring with protective cover to be mounted with a torque of 0.4 Nm onto

actuator


Max. 3 switching elements can be clipped on The lamp block will be delivered with screw terminal

max. number of switching


elements:

3

Wiring diagrams:




Mounting cut-outs:



A = Screw terminal

B = Push-in terminal (PIT)
C = Plug-in terminal 6.3 mm x 0.8 mm
D = Double plug-in terminal 6.3 mm x 0.8

### Dimension drawings:



A = Screw terminal