

Actuator

704.062.718











704.062.718 Actuator

EB	1	NI	т.	
ГΠ	V	IA		

Front dimension: Ø 35 mm

Front form: Round

Front bezel colour: Nature

Front bezel material: Aluminium

MOUNTING

Design: Flush

Mounting cut-out: Ø 30.5 mm

Mounting type: Panel mounting

OPERATING-/INDICATION PART

Lens colour: Colourless

Lens material: Plastic

Lens illumination: Illuminated

Lens shape: Flush

Lens optics: transparent

ELECTRICAL CHARACTERISTICS

Standards: The switches comply with the "Standards for low-voltage switching devices" DIN


EN 60947-1

MECHANICAL CHARACTERISTICS

Switching action: Maintained

Mechanical lifetime: ≤3 Mil. cycles of operation 8 N Operating force: **Operating Travel:** ca. $5.8 \text{ mm} \pm 0.2 \text{ mm}$ Weight: 0.046 kg **AMBIENT CONDITION IP Protection:** IP65 front side - 40 °C ... + 55 °C Operating temperature: – 40 °C ... + 85 °C Storage temperature: **CERTIFICATE REACH:** REACH compliant RoHS: RoHS compliant **OTHER Short Description:** Actuator, Ø 30.5 mm, Ø 35 mm, Flush, Illuminated, Colourless, Plastic, transparent, Round, Nature, Aluminium, anodised, Maintained Housing colour: Grey Plastic Housing material: Hints: Max. 3 switching elements can be clipped on The lamp block will be delivered with screw terminal The colour of anodised aluminium parts can vary due to technical production reasons max. number of switching 3 elements: Wiring diagrams:


Mounting cut-outs:



A = Screw terminal

B = Push-in terminal (PIT)
C = Plug-in terminal 6.3 mm x 0.8 mm
D = Double plug-in terminal 6.3 mm x 0.8

Dimension drawings:



A = Screw terminal