

Actuator

704.121.018











704.121.018 Actuator

_	_	_		-
-	к	u	N	

Front dimension: Ø 35 mm

Front form: Round

Front bezel colour: Nature

Front bezel material: Aluminium

MOUNTING

Design: Flush

Mounting cut-out: Ø 30.5 mm

Mounting type: Panel mounting

ELECTRICAL CHARACTERISTICS

Standards: The switches comply with the "Standards for low-voltage switching devices" DIN

EN 60947-1

MECHANICAL CHARACTERISTICS

Switching action: Rest (a) - Maintained

Switching positions: 2 positions

Switching angle: $90^{\circ} \text{ right } / -45^{\circ} \dots +45^{\circ}$


Mechanical lifetime: ≤50 000 cycles of operation

Weight: 0.103 kg

AMBIENT CONDITION


IP Protection: IP65 front side

Operating temperature:	– 40 °C + 55 °C
Storage temperature:	– 40 °C + 85 °C
CERTIFICATE	
REACH:	REACH compliant
RoHS:	RoHS compliant
OTHER	
Short Description:	Actuator, Ø 30.5 mm, Ø 35 mm, Round, Nature, Aluminium, Rest (a) - Maintained
Hints:	The standard lock Ronis 251 Further lock numbers on request Max. 3 switching elements can be clipped on
max. number of switching elements:	3
Switching positions:	0 1



Wiring diagrams:


Mounting cut-outs:



A = Screw terminal

B = Push-in terminal (PIT)
C = Plug-in terminal 6.3 mm x 0.8 mm
D = Double plug-in terminal 6.3 mm x 0.8

Dimension drawings:



A = Screw terminal