

## Actuator

704.731.0











# 704.731.0 Actuator

FRONT	
Front dimension:	30 mm x 30 mm
Front form:	Square
MOUNTING	
Design:	Raised
Mounting type:	Panel mounting
OPERATING-/INDICATION PART	
Lens illumination:	Illuminated
ELECTRICAL CHARACTERISTICS	
Standards:	The switches comply with the "Standards for low-voltage switching devices" DIN EN 60947-1
MECHANICAL CHARACTERISTICS	
Switching action:	Momentary
Mechanical lifetime:	≤3 Mil. cycles of operation
Operating force:	8 N
Operating Travel:	ca. 5.8 mm ± 0.2 mm
Weight:	0.008 kg

## **AMBIENT CONDITION**

IP Protection: IP65 front side

**Operating temperature:**  $-40 \, ^{\circ}\text{C} \, ... + 55 \, ^{\circ}\text{C}$ 

Storage temperature: - 40 °C ... + 85 °C

#### **CERTIFICATE**

**REACH:** REACH compliant

RoHS: RoHS compliant

### **OTHER**

**Short Description:** Actuator, 30 mm x 30 mm, Illuminated, Square, Momentary

Housing colour: Black

Housing material: Plastic

Hints: Max. 3 switching elements can be clipped on

max. number of switching


elements:

3

Wiring diagrams:



Mounting cut-outs:



A = Screw terminal


B = Push-in terminal (PIT)

C = Plug-in terminal 6.3 mm x 0.8 mm


D = Double plug-in terminal 6.3 mm x 0.8

mm

Dimension drawings:



A = Screw terminal



A = Screw terminal