

Actuator

84-0090.7









Your product:



84-0090.7 Actuator

FRONT

Front dimension: Ø 25 mm

Front form: Round

Front bezel colour: Colourless

Front bezel material: Plastic

MOUNTING

Design: Flush

Mounting cut-out: Ø 22.5 mm

Mounting type: Panel mounting

MECHANICAL CHARACTERISTICS

Tightening torque: Fixing nut 0.8 Nm

Weight: 0.008 kg

AMBIENT CONDITION

IP front protection: IP67

IP Protection: IP67

Operating temperature: $-25 \, ^{\circ}\text{C} \, ... + 70 \, ^{\circ}\text{C}$

Storage temperature: $-40 \,^{\circ}\text{C} \dots + 85 \,^{\circ}\text{C}$

Climate resistance: Damp heat, cyclic: 96 hours, + 25 °C/97 %, + 55 °C/93 % relative humidity, as per

EN IEC 60068-2-30

Damp heat, steady: 56 days, + 40 °C/93 % relative humidity, according to EN IEC

60068-2-78

Rapid change of temperature: 100 cycles, - 40 °C ... + 80 °C, as per EN / IEC

60068-2-14

CERTIFICATE

Approbations: EBC (TSI PRM), NFF

Conformities: CE, UKCA, 2011 / 65 / EC (RoHS)

REACH: REACH compliant

RoHS: RoHS compliant


OTHER

Short Description: Actuator, Ø 22.5 mm, Ø 25 mm, Round, Colourless, Plastic, translucent, IP67


Hints: Front bezel illuminated

Description component: Material housing actuator: Plastic as per UL94 V0


Wiring diagrams:



Mounting cut-outs:




Dimension drawings:



A = Plug-in terminal 2.8 mm x 0.8 mm B = Flat ribbon cable

E = Lens raised above bezel

G = Lens convexe raised above bezel



E = Lens raised above bezel G = Lens convexe raised above bezel