

# Stop switch

Distribution by Farnell



84-6241.2B40







# 84-6241.2B40 Stop switch

Е	D	0	N	٦
г	п	v	14	

Front dimension: Ø 32 mm

Front form: Round

## **MOUNTING**

**Mounting cut-out:** Ø 22.3 mm

# **OPERATING-/INDICATION PART**

Lens colour: Grey

**Lens material:** Plastic, according to UL 94 V0

Lens illumination: Illuminated

**Lens shape:** Mushroom-head

Lens optics: opaque

Lens: round

Switching position ring: Black

Illumination colour: Red

# **ELECTRICAL CHARACTERISTICS**

Switching voltage and switching current:

Switch rating AC with silver contact (gold plated) Service category AC-15 as per EN IEC 60947-5-1

120 VAC 240 VAC Voltage 1,5 A Current 3 A

Switch rating AC with silver contact (gold plated) Service category DC-13 as per EN IEC 60947-5-1

NO/NC contacts NO contacts NC contacts

(48 VA) (60 VA)

12 VDC/2.0 A 12 VDC/2.5 A 125 VDC/0.22 A 24 VDC/2.0 A 24 VDC/2.5 A 250 VDC/0.11 A 48 VDC/1.0 A 48 VDC/1.25 A

60 VDC/0.8 A 60 VDC/1.0 A

**Contacts:** 2 NC

Operating voltage: 5 - 30 V DC (LED)

**Operation current:** 9,7 - 12,4 mA

**Rated Operational Voltage Ue:** 250 VAC/DC according to EN IEC 60947-1

Rated impulse withstand voltage

Uimp:

4 kV, according to EN IEC 60947-1

Rated insulation voltage Ui: 250 V according to EN / IEC 60947-1

Rated short-circuit current

caused:

1 000 A, type of short-circuit device 6 A gG (EN 60947-5-1)

Recommended minimum

Silver contacts (gold plated) operational data:

Voltage 1 VAC/DC Current 1 mA

Switching rating: 250 V AC @ 1,5 A

**Electrical lifetime:** 50 000 cycles of operation

**Electric strength:** 500 VAC, 50 Hz, 1 minute according to DIN IEC 60512-2

Overvoltage category: III, according to EN / IEC 61058-1

Pollution degree: 3, according to EN IEC 60947-1

Protection class: II, according to EN / IEC 60947-5

Standards: According to EN 60947-5-1, EN 60947-5-5, DIN EN ISO 13850, EN IEC 60204

Thermal current Ith: 5 A

### **MECHANICAL CHARACTERISTICS**

Flat ribbon cable 300 mm Terminal:

**Contact material:** Gold

Switching action: Maintained

Switching system: Slow-make switching element

Release type: Twist to unlock

Mechanical lifetime: ≥50 000 cycles of operation Operating force: 20 N  $\pm$ 4 N

Operating Travel: ca. 4 mm

**Tightening torque:** Fixing nut 0.8 Nm

**Weight:** 0.036 kg

#### **AMBIENT CONDITION**

IP front protection: IP65, IP66, IP67, according to DIN EN 60529

**IP Protection:** IP20 rear side

**IK Protection:** IK07 as per IEC 62262

**Operating temperature:**  $-25 \, ^{\circ}\text{C} \, ... + 70 \, ^{\circ}\text{C}$ 

Storage temperature:  $-25 \,^{\circ}\text{C} \dots + 85 \,^{\circ}\text{C}$ 

Shock resistance: Max. 150 m / s<sup>2</sup>, pulse width 11 ms, 3-axis, (semi-sinusoidal as per EN IEC 60068-

2-27

Vibration resistance: Max. 50 m / s<sup>2</sup> from 10 Hz ... 500 Hz, 10 cycles, 3-axis (sinusoidal EN IEC 60068-

2-6)

Climate resistance: Damp heat, cyclic: 96 hours, + 25 °C/97 %, + 55 °C/93 % relative humidity, as per

EN IEC 60068-2-30

Damp heat, steady: 56 days, + 40 °C/93 % relative humidity, according to EN IEC

60068-2-78

Saline mist: 96 hours, + 35 °C in chemical solution NaCl, as per EN IEC 60068-2-

11

Dry heat: 96 hours, + 70 °C, as per EN IEC 60068-2-2

Low temperature: 96 hours, - 40 °C (as per EN IEC 60068-2-1)

## CERTIFICATE

**Approbations:** CB (IEC 60947-5-1. IEC60947-5-5), CCC, UL NKCR

**Conformities:** CE, 2006 / 42 / EC (MD), 2011 / 65 / EC (RoHS)

**REACH:** REACH compliant

RoHS: RoHS compliant

### **OTHER**

 $\textbf{Short Description:} \hspace{1.5cm} \textbf{Stop switch, } \varnothing \ 22.3 \ \text{mm, } \boxtimes 32 \ \text{mm, } \text{Mushroom-head, Illuminated, Grey, Plastic,} \\$ 

according to UL 94 V0, opaque, Round, 2 NC, Maintained, Flat ribbon cable 300 mm, IP65, IP66, IP67, according to DIN EN 60529, Twist to unlock, Red

min, ir 65, ir 66, ir 67, according to bin Lin 66529, twist to unlock, he

Material: Plastic, according to UL 94 V0

Housing colour: Grey

**Housing material:** Plastic, according to UL 94 V0

Product attributes: Twist to unlock clockwise, position indication ring black

Hints:

Twist to unlock clockwise

Luminosity and wave length variations caused by LED manufacturing processes may cause slight differences regarding the illumination.

Foolproof according to EN IEC 60947-5-5


Lens colour Red

Standard version: Flat ribbon-cable length 300 mm or plug-in terminal 2.8 mm x 0.5 mm


**Description component:** 

The double-break switching system can be supplied for the following switching functions: 1 Normally closed, 2 Normally closed, 1 Normally closed + 1 Normally open. The Normally closed contacts have forced opening according to EN 60947-5-5, Material housing actuator: Plastic as per UL94 V0, Material lens: Plastic as per UL94 V2

Wiring diagrams:



**Component layouts:** 



A = Cable

B = white

C = brown

D = green E = yellow


F = grey

G = pink

H = Terminals

I = Illumination

## Mounting cut-outs:



## **Dimension drawings:**

