

Your Expert Partner for Human Machine Interfaces





https://farnell.eao.com/p/84-8001.9620

Your product:



84-8001.9620 Indicator element

OPERATING-/INDICATION PART	
Illumination colour:	White
ELECTRICAL CHARACTERISTICS	
	24 V DC ±10 %
Operating voltage:	24 V DC ±10 %
MECHANICAL CHARACTERISTICS	
Terminal:	Plug-in terminal, 2.8 x 0.8 mm
Weight:	0.005 kg
AMBIENT CONDITION	
IP Protection:	IP40
CERTIFICATE	
REACH:	REACH compliant
RoHS:	RoHS compliant
OTHER	
Short Description:	Indicator element, White, Single-LED, 24 V DC ± 10 %, Plug-in terminal, 2.8 x 0.8 mm
Kind of illlumination:	Single-LED
Hints:	LED and built-in resistor included,Standard version: Cable length 300 mm,Other
	options on request: Customisation of cable and connectors, rear side fully sealed (IP 67),Protection degree (rear side): IP 40, upgrade to IP 67 with plug Part No. 84- 900 possible. With applications where strong vibrations occure, the plugs may become loose,Luminosity and wave length variations caused by LED

manufacturing processes may cause slight differences regarding the illumination. The customer has to decide what resistor shall be used to the LED

Wiring diagrams:

