

Capacitive sensor switch with IO-Link Stainless Steel

Distribution by Farnell



84-ADKS-B15-04AF





https://farnell.eao.com/component/84-ADKS-B15...

Your product:



84-ADKS-B15-04AF Capacitive sensor switch with IO-Link Stainless Steel

FRONT

Front dimension:	Ø 30 mm
Front form:	Round
Front bezel material:	Stainless steel 316L

MOUNTING

Design:	Flush
Mounting cut-out:	Ø 22.5 mm
Mounting type:	Panel mounting

OPERATING-/INDICATION PART

Lens material:	Plastic
Lens illumination:	Illuminated
Lens shape:	Flush
Lens optics:	transparent
Symbol:	arrows (B15)

ELECTRICAL CHARACTERISTICS

Operating voltage:	8.4 - 32 V DC
Communication interface:	IO-Link specification

MECHANICAL CHARACTERISTICS

Terminal:

Connector M12

Switching system:	Capacitive
Operating force:	No actuating force necessary
Weight:	0.015 kg

AMBIENT CONDITION


IP front protection:	IP69K
IK front protection:	IK08
Operating temperature:	– 30 °C + 65 °C
Climate resistance:	Relative humidity, max. 95%, non-condensing


CERTIFICATE


Approbations:	CSA, EHEDG
Conformities:	CE, UKCA
REACH:	REACH compliant
RoHS:	RoHS compliant


OTHER


Short Description:	Capacitive sensor switch with IO-Link Stainless Steel, Ø 22.5 mm, Ø 30 mm, Flush, Illuminated, Plastic, transparent, Round, Stainless steel 316L, Connector M12, IP69K, IK08, arrows (B15)	
Housing colour:	Black	
Housing material:	Plastic	
Wiring diagrams:	3-pole	5-pole












Mounting cut-outs:



Dimension drawings:

