


# Switching element

96-323.837

Distribution by  
Farnell



<https://farnell.eao.com/component/96-323.837/...>

Your product:

---



## 96-323.837

### Switching element

#### PRODUCT RANGE

**Product Status:** Phase-out

#### ELECTRICAL CHARACTERISTICS

**Contacts:** 1 C

**Contact resistance:** New state  $\leq 100 \text{ m}\Omega$ , as per DIN / IEC 60512-2-2b

**Switching rating:** 42 V DC @ 0,1 A

**Electrical lifetime:**  $\geq 5 \times 100\,000$  cycles of operation at 30 VDC, 100 mA, according to IEC 61058-1

**Electric strength:** 500 VAC, 50 Hz, 1 minute, as per IEC 60512-2-11 between all terminals and earth

**Thermal current I<sub>th</sub>:** 100 mA

#### MECHANICAL CHARACTERISTICS

**Terminal:** PCB terminal

**Contact material:** Gold

**Switching system:** Snap-action switching element

**Switching system:** Single-break, self-cleaning, snap-action switching element with tactile feel of operation.

**Mechanical lifetime:**  $\geq 5 \text{ Mil.}$  cycles of operation, according to IEC 60512-5-9a

**Operating force:** 1.4 N  $\pm 0.3$  N


**Operating Travel:** Lead distance 1.0 mm  $\pm 0.3$  mm, Total distance 1.7 mm  $\pm 0.5$  mm

**Weight:** 0.002 kg

#### AMBIENT CONDITION

**IP front protection:** IP67, according to IEC 60529





**Dimension drawings:**

